

A noval concept based on Regenerative braking





N. Satheesh kumar


Dr. Michael Schier






| Introduction | Methodology | Design | Results | Conclusion |

Problem: Consumers are not buying EVs




of responded cited poor cruise range


Source: VroomVroomVroom




Source: i-MiEV's cruise range performance (Mitsubishi Motors)




Methodology





Introduction | Methodology | Design | Results | Conclusion |







Drive Motor

The setup allows the compressor motor to be deactivated during deceleration and the A/C to be driven by recovered **Kinetic Energy**



Introduction | Methodology | Design | Results | Conclusion |

Other advantages of integration


- Elimination of separate cooling system for electronic control unit
- Shared speed control unit
- Elimination of external cables
- Single housing for compressor, drive unit and electronic unit
- Weight and space savings
- Reduced parts count and increased reliability



A/C Compressor




Drive Motor




| Introduction | **Methodology |** Design | Results | Conclusion |

Drive cycle	Distance travelled (km)	Total time (sec)	Braking time (sec)	% braking time	Average Pgen (kW)
ECE 15	1.0	195	39-4	20.5%	1.5
EUDC	7.0	400	45.0	11.3%	2.9
EUDC, low power	10.6	1224	101.0	8.3%	3.8
ECE 15 + EUDC	10.9	1225	202.1	16.5%	1.9
NEDC	10.9	1184	201.3	17.0%	1.8

Design





Introduction | Methodology | Design | Results | Conclusion |



Schematic Representation

| Introduction | Methodology | Design | Results | Conclusion |






Patent: Antriebsmotor fur Elektrofahrzeuge mit integriertem Kilmakompressor.

Patent No.: Europe A 63 630 j





Introduction | Methodology | Design | Results | Conclusion |



Conclusion

Introduction | Methodology | Design | Results | Conclusion |

Poor cruise performance of the Electric Vehicles continues to be the primary reason for its low market penetration among general public.

The design leverages on concentric placement of compressor and traction drives. Further, the existing SVC is redesigned to enhance efficiency.

Introduction

Methodology

Design

Results

Energy
conversations are
eliminated to
improve the
efficiency.

The energy drawn from the battery is reduced by 3.2%.

