

Automatic Enrichment of Ontology for Engineering Design Process

Kobkaew Opasjumruskit
German Aerospace Center (DLR)
Institute of Data Science

SEMANTiCS 2019, September 9-12
Karlsruhe



Knowledge for Tomorrow




Agenda

- Scenario
- Ontology for Satellite Design Process
 - Structure & Current Development
- Automatic Improvement of Ontology
 - ConTrOn – Continuously Trained Ontology
- Summary & Outlook





Concurrent Engineering Facility



Model Based System Engineering Tool

Challenge #1 Heterogeneous Formats

OVERVIEW

Under a grant from the Defense Production Act Title III, Ball is developing a new line of affordable, fully-domestic star trackers: CT-2020.

Domestically-sourced, secure solution

Utilizing all U.S. trusted suppliers, secure systems and flight software, the CT-2020 is an assured, fully U.S.-sourced solution for the nation's most important missions.

Low cost, high performance

Blending medium and high accuracy star tracker heritage in a compact, fully-integrated package, CT-2020 offers high performance and operational flexibility at a competitive price point.

CT-2020 integrates the latest high-efficiency Complementary Metal Oxide Semiconductor (CMOS) detector technology developed in the U.S. specifically for star trackers, enabling the CT-2020's cost-effective small mass and volume design.

Operational flexibility, on-orbit upgrades

Featuring operational flexibility, CT-2020 provides customers two modes of operation: fully autonomous attitude and directed search, in which the user can select certain regions of interest. In autonomous attitude mode, the tracker can achieve single head accuracies in the realm of 1 arcsec, with even higher accuracies in directed search mode.

CT-2020's robust software features an on-orbit environment simulator, allowing the tracker to emulate mission-specific integration and operations for risk reduction. In addition, the tracker's software can be upgraded while on-orbit, allowing updates to the star catalog, spatial/intensity calibration and software algorithms.

HERITAGE

For more than 40 years, Ball has delivered the highest-reliability, highest-performance star trackers available to support civil, commercial and defense missions. We are leveraging this heritage to optimize the CT-2020 for cost and performance to bring an affordable, domestic star tracker solution to the U.S. market.


Expected availability of the CT-2020 is fourth quarter of 2019.

Ball Aerospace
303-939-6100 • Fax: 303-939-6104 • info@ball.com • www.ball.com/aerospace

SPECIFICATIONS

- 1 arcsec performance stand-alone unit
- Provides full three-axis ± 1.0 arcsec performance with typical two-tons on a spacecraft
- Full performance with a 15 deg sun angle
- Tracks with moon in field of view
- High rate capable (up to 8 deg/sec) with reduced performance to enable track-through-slew
- 1553, RS-422 command and data interfaces, SpaceWire option
- Simultaneous attitude output and full frame image output at 10 Hz over high speed LVDS
- On-orbit upgradable software, star catalog, algorithms and spatial re-calibration
- TEC provides efficient, stable detector temp control, on-orbit adjustable
- Hardware-in-the-loop testing with built-in focal plane simulator enables end-to-end mission simulations
- Integrated LED polarity tester
- Two modes of operation: fully autonomous or directed search
- Mass: 3 kg
- Power: 8 W
- Modular options:
 - Nominal +28 V power, +120 V, +5 V options
 - Three sun shade options (15, 20, 30 deg)
 - Q or V-Level parts with full EEE parts traceability
- Radiation-hardened-by-design CMOS and ASIC
- Meets all relevant MIL-STD and SMC requirements
- Complete set of documentation and analysis available with production

SYSTEM COMPONENTS



Copyright © 2018, Ball Aerospace | 01408

μSTAR Tracker

APPLICATIONS

- Satellite Attitude and Rate Determination
- GEO and LEO Satellite Orbits
- Long Duration/High Reliability Missions

SOFTWARE FEATURES

- Star Identification Based on Pyramid Code
- Integrated Systematic Error Correction Allows for High Accuracy
- Real-Time On-orbit Calibration Accounts for Degradation
- Extended Kalman Filter Produces Attitude and Rate Estimates
- Less Sensitive to Spurious Signals and Upsets

CONFIGURATION OPTIONS

Feature	MIST	uStar-100M	uStar-200M	uStar-200H	uStar-400M
FPA	Ruby	HA52	HA52	HA52	HA52
Accuracy [3 σ]	30 arcsec	5-20 arcsec	1-20 arcsec	< 1 arcsec	1-5 arcsec
Average Power	<3W	<5 W	8-10 W	< 10 W	< 18 W
Update Rate	10 Hz	1 Hz	10 Hz	10 Hz	100 Hz
DPE Mass (kg)	0.5	0.9	1.2	1.2	1.2
CHU Mass (kg)	Integrated Unit	0.9	0.9	1.5	2.1
Total (kg)	0.5	1.8	2.1	2.7	3.3

*Contact Warehouse for availability

RADIATION TOLERANCE

Total Ionizing Dose (TID)	> 100 and 300 krad (option)
Single Event Latchup (SEL)	> 80 MeV/mg/cm ²
Single Event Upset (SEU)	< 10 ⁻⁹ errors/system-day
Neutrons	> 2x10 ¹² n/cm ²

SUPPORTING ELECTRONICS

The μSTAR™ features proven, high performance, radiation hardened supporting electronics to ensure accurate, reliable functionality in the harsh space environment.

PROTON 200K™ RADIATION HARDENED SPACE COMPUTER

The Proton200K™ space computer is flight-proven, high speed, and radiation hardened to provide extraordinary performance benefits by removing the barriers associated with commercial processor offerings. It is a qualified space computer for onboard data processing with 1.8 GFLOPS @ 200 MHz Floating Point, 900 MFLOPS @ 200 MHz with SEU mitigated to 1E-4 errors/day



Specifications Subject to Change Without Notice

4/9/2015



Size & Mass		
Dimensions	154 mm x 154 mm x 237 mm	including baffle
Mass	approx. 2 kg	including baffle, GEO-shielding, OCDC-converter, MIL1553
Imaging System Design		
Optics	refractive, focal length 43 mm, f/1.2	spherical lens technology, rad-hard glass material
Detector Resolution	1024 x 1024 pixels	
Field of View	20 deg	circular
Detector Options	HA52	APS CMOS radiation tolerant
	SHAD-2000	APS CMOS radiation hard
Temperature Range		
Operational	-30 °C ... +60 °C	typical cooler controller set point at TAPS++30°C
Non-operational	-40 °C ... +70 °C	
Attitude Performance		
Random Error	< 1 arcsec [1- σ] across boresight < 8 arcsec [1- σ] boresight	includes LSFE, HSFE, TE
Blas Error	< 5 arcsec, all axes	over full operational temperature range
Acquisition Time	< 10 sec, after switch-on < 5 sec, in-acquisition "Test in space"	direct entry to attitude tracking with spiori information
Slew Rate & Acceleration	0.3 deg/sec, 0.3 deg/sec ² 1.0 deg/sec, 0.2 deg/sec ² 6.5 deg/sec, 1.7 deg/sec ²	STAR1000 single head capability SHAD single head capability
Sensitivity	6.0m G0-reference star	end of life performance
Sampling Rate	10 Hz 16 Hz	others up to 32 Hz on demand
Shay Light	Sun: 20 deg exclusion angle Earth: < 2.0 deg Moon: accepted in field of view	full cone depending on orbit height and Earth illumination conditions
Interfaces		
Data	MIL-STD-1553B RS422	optional, selectable, others on demand
Power	28V nominal 150V nominal 50V nominal	optional selectable for either regulated or unregulated primary power s&C bus architectures other voltages on demand
Power Consumption		
MIL-STD-1553B	< 6 W, Pelletier Cooler OFF	end of life
data interface	< 1.2 W, Pelletier Cooler ON/HX	
RS422	< 5 W, Pelletier Cooler OFF	end of life
data interface	< 1.1 W, Pelletier Cooler ON/HX	
Operations		
Reliability	460 FIT, Tu@20°C	with Class 1 EEE parts
Operational Modes	Boot Standby-Mode Autonomous Attitude Determination (AAD) Nominal Attitude Tracking (NAT) Photo, Upload/Download, Self-Test	fully autonomous mode switch from Power-On to NAT by software parameter set-up possible



Jenaopttronik GmbH • Otto-Eberstein-Straße 3 • 07745 Jena • Germany
Phone +49 3641 200-110 • Fax +49 3641 200-222
Email sales@jena-opttronik.de • Web www.jena-opttronik.com

Challenge #2 Standard description

ECSS-E-ST-60-20C –
Star sensor terminology and performance specification

3.2.7.2 correct attitude threshold

maximum quaternion absolute measurement error (AMEq) for which an attitude is a correct attitude

3.2.7.3 false attitude

attitude which is a non correct attitude



3.2.7.4 false star


signal on the detector not arising from a stellar source but otherwise indistinguishable from a star image

NOTE This definition explicitly excludes effects from the Moon, low incidence angle proton effects etc., which can generally be distinguished as non-stellar in origin by geometry.

3.2.7.5 image output time

time required to output the detector image

- Not machine-interpretable
- Require manual efforts transferring data into tools




The background features a dark, semi-transparent overlay on top of technical drawings. On the left, a table with multiple rows and columns of text is visible. On the right, there are architectural or engineering drawings with various lines and shapes. The overall scene suggests a technical or engineering context.

#1 ONTOLOGY FOR SATELLITE PARTS


Ontology: Sources

- Data models developed by DLR's in-house MBSE tool
 - <https://github.com/virtualsatellite>
- Existing product description standards
- Actual product data sheets
- Interview with system engineers and manufacturers
- Current version: <https://zenodo.org/record/2616374>




Ontology: Hierarchical Structure

Spacecraft parts ontologies




Spacecraft Parts Ontology: Core

- Common attributes for all parts
 - Mass
 - Lifetime
 - Operating Temperature
 - Width, Height, Length
- 26 attributes



Spacecraft Parts Ontology: Star Tracker

- Specific attributes to star trackers
 - Attitude accuracy
 - Field of view
 - SNR
 - Etc.
- 36 Attributes



However, as time flies



People change, products change



And ontology should evolve


But, how ...



Auto-Improvement of ontology



#2 AUTO-IMPROVEMENT OF ONTOLOGY



Information Extraction

- Natural Language Processing
- Semantic Knowledge

Existing Tools: Entities Extraction

DBpedia Spotlight



The ASTRO APS has been designed with compact dimensions, low mass, and low power consumption. Since July 2013, the ASTRO APS has been accumulating space heritage operating flawlessly on board of Alphasat.



Jena-Optronik GmbH · Otto-Eppenstein-Straße 3 · 07745 Jena · Germany
 Phone +49 3641 200-110 · Fax +49 3641 200-222
 Email sales@jena-optronik.de · Web www.jena-optronik.com

The Jena-Optronik **ASTRO** APS is an Autonomous Star Sensor with the most advanced **radiation hard CMOS** Active Pixel Sensor detector technology for long-term missions on Telecom, Science and **Earth** Observation satellites. space for success
 The **ASTRO** APS has been designed with **compact** dimensions, low mass, and low power consumption.
 Since http://dbpedia.org/resource/American_Society_for_Radiation_Oncology **space heritage** operating **flawlessly** on board of **Alphasat**.

Picture Alphasat © ESA

Jena-Optronik GmbH

Phone +49 3641 200-110

Email sales@jena-optronik.de

Size & Mass

Dimensions 154 mm


Mass approx. 2 kg

OPEN CALAIS

ESA Contact Details Company Technology

RELATION CONTACT DETAILS

telephone	+49 3641 200-110
emailaddress	sales@jena-optronik.de
url	www.jena-optronik.com



Domain Knowledge Extractor




data, power, mm, space, receiver, temperature, mass, thruster, radiation, noise, battery, weight, **magnetic_field**, reliability, **data_rate**, payload, telemetry, resolution, thermal, baffle, lifetime, gauss, **data_rates**, **propulsion_system**, tracker, solar




- Extract keywords
 - Bag-of-words
 - Tf-idf



Definition, Synonyms, Hypernyms, ...



- Word Disambiguation
 - <https://wordnet.princeton.edu/>
 - Part-of-Speech Tagging
 - Vector Space Model



Ontology Enricher



- If ambiguous (multiple entities matched), compare to domain knowledge keywords
- At this step, only enriching the existing classes

Information Extractor



Standard NST

Attitude Solution	5 Hz	
Sky Coverage	> 99 %	
Mass	0.35 kg w/ baffle	●
Volume	10 x 5.5 x 5 cm	
Peak Power	< 1.5W	●
Field of View	10 x 12 degrees	●
Sun Keep Out	45 degrees (half cone)	●
Design Life		● > 5 Years (LEO)

- Search text based on ontology classes
 - Name, label, superclass, same as
- Extract values that come after keywords

Extraction approach	Extracted property-value pairs			Recall	Precision	F-measure
	Ideal	Extracted	Correctly extracted			
ConTrOn		427	256	0.94	0.6	0.73
Text-based search	271	542	263	0.97	0.49	0.65

- Need human-in-the-loop: Next

Key-Value Pattern Learner


- Users provide feedback via a UI (human-in-the-loop)

The screenshot shows the Jena-Optronic Astro 15 product page. On the left, there are technical specifications under various headings like 'Dimensions', 'Mass', 'Optical design', 'Temperature range', and 'Performance'. On the right, there is a feedback form with fields for 'Key', 'Value', 'Remarks', and 'Comments'. The 'Key' field contains 'Lens', the 'Value' field contains 'focal length 55 mm', and the 'Remarks' field is empty. Below the form is a 'View entry' button. At the bottom right, there is a table with columns for 'Key', 'Value', and 'Remarks'.

Key	Value	Remarks
Dimensions	192 mm Ø x 496 mm	Sensor with 30" Baffle
Mass	4350 g f	Sensor without Baffle
Lens	focal length 55 mm	

- Key → Add to the ontology
 - Enrich by adding new classes

- Value → Improve the information extraction



Pattern Example

179 x 75 x 112 mm



154 mm x 154 mm x 237 mm

25 x 10 x 10 cm

- Learned patterns
 - `<number>+" x "+<number>+" x "+<number> + <unit>`
 - `<number> <unit>+" x "+<number> <unit>+" x "+<number> <unit>`
- Verify the pattern
 - Apply to the information extractor
 - Choose the pattern that yield the minimum error

Summary

- Current satellite parts ontology is available at:
<https://zenodo.org/record/2616374>
- ConTrOn: automatically improve ontology from data sheets
 - ✓ Ontology Enrichment
 - ✓ Domain Knowledge Extraction
 - ✓ Ontology-based Information Extraction
 - ☐ Key-Value Pattern Learner (human-in-the-loop)



Outlook

- Collecting feedbacks from users
 - Baseline for evaluation of information extraction
- Extension of ontology
- Knowledge graph from data sheets



kobkaew-opas



kobkaew.opasjumruskit@dlr.de



kobkaewo

Thank you for your attention!