

Improvement in flowability of Thermo-chemical storage material by using Nanostructured additives

By

BIPIN VISHWESWARAIH ANGADI

Submitted to the University of Augsburg

In partial fulfillment of the requirements for the degree of

Master of Science in Material Science

Supervisors

Marie Gollsch

DLR (Deutsches Zentrum
für Luft- und Raumfahrt)

Prof. Siegfried R. Horn

University of Augsburg

Statutory declaration (according to § 20 Par. 5 FPO)

I solemnly declare that the research done in this thesis was completely on my own without the use of external sources that have not been mentioned or cited in this thesis and its present form has not been submitted or accepted formerly for the award of a degree or diploma in this or any other tertiary institute and is not being submitted for a degree or diploma at this institution.

Start of Thesis: 1st August, 2014

End of thesis: 28th February 2015

Signature of the Author _____

Bipin Vishweswaraih Angadi

Certified by _____

Prof. Dr. Siegfried R. Horn
University of Augsburg

Supervised by _____

Ms. Marie Gollsch
DLR Stuttgart

Examined by _____

Mr. Marc Linder
DLR Stuttgart

Approved by _____

Chairperson or Deputy Chairperson of Master Examination Board

Place and Date _____

Following experiments were carried out at DLR Stuttgart and University of Siegen, from 1st August 2014 to 28th February 2015.

Contents

I.	ABSTRACT.....	V
II.	ACKNOWLEDGEMENT	VI
III.	Nomenclature	VII
IV.	List of Figures	VIII
V.	List of Tables	XI
1.	MOTIVATION.....	1
2.	THEORY AND LITERATURE REVIEW	2
2.1	Thermal Energy Storage.....	2
2.1.1	Thermo-Chemical Storage.....	3
2.2	Flowability.....	4
3.	MATERIALS.....	9
3.1	CaO/Ca(OH) ₂ as thermochemical storage.....	9
3.2	Additives.....	10
4.	METHODS	13
4.1	Mixing	13
4.2	Flowability Test.....	14
4.3	Tube furnace	17
4.4	Thermo-gravimetric analysis.....	18
4.5	Scanning Electron Microscopy.....	19
4.6	X-Ray Powder Diffraction	22
4.7	Static Laser Scattering Particle Size Distribution	24
4.8	Gas Pycnometry.....	26
4.9	Differential Calorimetric Analysis	27
5.	RESULTS	30
5.1	Mixing	30
5.2	Powder Flow Tester.....	31

5.2.1	Aeroxide [®] Alu C	31
5.2.2	Aerosil [®] COK 84	33
5.2.3	Aerosil [®] 200.....	35
5.2.4	Aeroxide [®] Alu 130.....	37
5.2.5	Boron nitride (BN).....	39
5.2.6	Silicon carbide (50-60 nm)	41
5.2.7	Silicon carbide (6.34 μm)	43
5.2.8	Silicon carbide (35.64 μm)	45
5.2.9	Magnesium Oxide.....	47
5.2.10	After cycling	49
5.3	Thermo Gravimetric Analysis	50
5.3.1	Aerosil [®] COK 84	50
5.3.2	Aerosil [®] 200.....	53
5.3.3	Aerosil [®] Alu 130.....	55
5.4	Scanning electron microscopy.....	57
5.4.1	Calcium hydroxide.....	57
5.4.2	Aerosil [®] COK 84.....	58
5.4.3	Aerosil [®] 200.....	59
5.4.4	Aeroxide [®] Alu 130.....	60
5.4.5	Aerosil [®] 300.....	61
5.5	X-ray powder diffraction.....	63
5.6	Static laser scattering particle size distribution	64
5.6.1	Calcium hydroxide.....	64
5.6.2	Aerosil [®] COK 84	65
5.6.3	Aerosil [®] 200.....	66
5.6.4	Aeroxide [®] Alu 130.....	67
5.6.5	Aerosil [®] 300.....	68
5.7	True Density	69

6.	DISCUSSION	71
6.1	Powder Flow Tester	71
6.2	Thermo Gravimetric Analysis	72
6.3	Scanning Electron Microscopy	73
6.4	X-Ray Powder Diffraction	74
6.5	Static laser scattering particle size distribution	75
6.6	True density	75
7.	CONCLUSION	76
8.	REFERENCES	78